



## DM54LS453A/DM74LS453A Quad 4:1 Multiplexer


### General Description

The quad 4:1 Mux selects one of four inputs, C0 through C3, specified by two binary select inputs, A and B. The true data is output on Y. Propagation delays are the same for inputs and addresses and specified for 50 pF loading. Outputs conform to the standard 8 mA LS totem pole drive standard.

### Features

- 24-pin SKINNYDIP saves space
- Twice the density of 74LS153
- Low current PNP inputs reduce loading
- 15 ns typical propagation delay

### Connection Diagram



TL/L/10226-1

Order Number DM54LS453AJ, DM74LS453AJ, DM74LS453AN or DM74LS453AV  
See NS Package Number J24F, N24C or V28A

### Function Table

Input Select		Outputs Y
B	A	
L	L	C0
L	H	C1
H	L	C2
H	H	C3

**Absolute Maximum Ratings** (Note 1)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

Supply Voltage $V_{CC}$	−0.5V to +7V (Note 2)
Input Voltage	−1.5V to +5.5V (Note 2)
Off-State Output Voltage	−1.5V to +5.5V (Note 2)
Input Current	−30.0 mA to +5.0 mA (Note 2)
Output Current ( $I_{OL}$ )	+100 mA
Storage Temperature	−65°C to +150°C

Ambient Temperature with Power Applied	−65°C to +125°C
Junction Temperature with Power Applied	−65°C to +150°C
ESD Tolerance	2000V
CZAP = 100 pF	
RZAP = 1500Ω	
Test Method: Human Body Model	
Test Specification: NSC SOP5-028	

**Recommended Operating Conditions**

Symbol	Parameter	Military			Commercial			Units
		Min	Nom	Max	Min	Nom	Max	
$V_{CC}$	Supply Voltage	4.5	5	5.5	4.75	5	5.25	V
$T_A$	Operating Free-Air Temperature	−55		125	0		75	°C

**Electrical Characteristics** Over Recommended Operating Conditions

Symbol	Parameter	Test Conditions		Min	Typ	Max	Units
$V_{IL}$	Low Level Input Voltage (Note 3)					0.8	V
$V_{IH}$	High Level Input Voltage (Note 3)			2			V
$V_{IC}$	Input Clamp Voltage	$V_{CC} = \text{Min}, I = -18 \text{ mA}$				−1.5	V
$I_{IL}$	Low Level Input Current	$V_{CC} = \text{Max}, V_I = 0.4 \text{ V}$				−0.25	mA
$I_{IH}$	High Level Input Current	$V_{CC} = \text{Max}, V_I = 2.4 \text{ V}$				25	μA
$I_I$	Maximum Input Current	$V_{CC} = \text{Max}, V_I = 5.5 \text{ V}$				1	mA
$V_{OL}$	Low Level Output Voltage	$V_{CC} = \text{Min}$	$I_{OL} = 8 \text{ mA}$			0.5	V
$V_{OH}$	High Level Output Voltage	$V_{CC} = \text{Min}$	$I_{OH} = -2 \text{ mA}$	MIL	2.4		V
			$I_{OH} = -3.2 \text{ mA}$	COM			
$I_{OS}$	Output Short-Circuit Current (Note 4)	$V_{CC} = 5 \text{ V}, V_O = 0 \text{ V}$		−30		−130	mA
$I_{CC}$	Supply Current	$V_{CC} = \text{Max}, \text{Outputs Open}$			60	100	mA

**Note 1:** Absolute maximum ratings are those values beyond which the device may be permanently damaged. Proper operation is not guaranteed outside the specified recommended operating conditions.

**Note 2:** Some device pins may be raised above these limits during programming operations according to the applicable specification.


**Note 3:** These are absolute voltages with respect to the ground pin on the device and include all overshoots due to system and/or tester noise. Do not attempt to test these values without suitable equipment.

**Note 4:** To avoid invalid readings in other parameter tests, it is preferable to conduct the  $I_{OS}$  test last. To minimize internal heating, only one output should be shorted at a time with maximum duration of 1.0 second each. Prolonged shorting of a high output may raise the chip temperature above normal and permanent damage may result.

# Switching Characteristics Over Operating Conditions


Symbol	Parameter	Test Conditions	Military			Commercial			Units
			Min	Typ	Max	Min	Typ	Max	
$T_{pd}$	Input to Output	$C_L = 50 \text{ pF}$		15	30		15	25	ns

## Test Load



TL/L/10226-2

## Test Waveform



TL/L/10226-3


### Notes:

$V_T = 1.5V$

$C_L$  includes probe and jig capacitance.

In the examples above, the phase relationships between inputs and outputs have been chosen arbitrarily.


## Schematic of Inputs and Outputs



TL/L/10226-4

# Logic Diagram

LS453A



TL/L/10226-5