

LM120/LM320 Series 3-Terminal Negative Regulators

General Description

The LM120 series are three-terminal negative regulators with a fixed output voltage of $-5V$, $-12V$, and $-15V$, and up to $1.5A$ load current capability. Where other voltages are required, the LM137 and LM137HV series provide an output voltage range of $-1.2V$ to $-47V$.

The LM120 need only one external component—a compensation capacitor at the output, making them easy to apply. Worst case guarantees on output voltage deviation due to any combination of line, load or temperature variation assure satisfactory system operation.

Exceptional effort has been made to make the LM120 Series immune to overload conditions. The regulators have current limiting which is independent of temperature, combined with thermal overload protection. Internal current limiting protects against momentary faults while thermal shutdown prevents junction temperatures from exceeding safe limits during prolonged overloads.

Although primarily intended for fixed output voltage applications, the LM120 Series may be programmed for higher output voltages with a simple resistive divider. The low quiescent drain current of the devices allows this technique to be used with good regulation.

Features


- Preset output voltage error less than $\pm 3\%$
- Preset current limit
- Internal thermal shutdown
- Operates with input-output voltage differential down to $1V$
- Excellent ripple rejection
- Low temperature drift
- Easily adjustable to higher output voltage

LM120 Series Packages and Power Capability


Device	Package	Rated Power Dissipation	Design Load Current
LM120/LM320	TO-3 (K)	20W	1.5A
	TO-39 (H)	2W	0.5A
LM320	TO-220 (T)	15W	1.5A
LM320M	TO-202 (P)	7.5W	0.5A

Typical Applications

Dual Trimmed Supply



Fixed Regulator



*Required if regulator is separated from filter capacitor by more than $3"$. For value given, capacitor must be solid tantalum. $25 \mu F$ aluminum electrolytic may be substituted.

†Required for stability. For value given, capacitor must be solid tantalum. $25 \mu F$ aluminum electrolytic may substituted. Values given may be increased without limit.

For output capacitance in excess of $100 \mu F$, a high current diode from input to output (1N4001, etc.) will protect the regulator from momentary input shorts.

— 5 Volt Regulators (Note 3)

Absolute Maximum Ratings

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications. (Note 5)

Power Dissipation Internally Limited
Input Voltage –25V

Input-Output Voltage Differential
Junction Temperatures
Storage Temperature Range
Lead Temperature (Soldering, 10 sec.)
Plastic

25V
See Note 1
–65°C to +150°C
300°C
260°C

Electrical Characteristics

Order Numbers		Metal Can Package												Power Plastic Package		
		LM120K-5.0 (TO-3)			LM120H-5.0 (TO-39)			LM320H-5.0 (TO-39)			LM320T-5.0 (TO-220)					
		1.5A 20W			0.5A 2W			0.5A 2W			1.5A 15W					
Parameter	Conditions (Note 1)											Units				
Output Voltage	$T_J = 25^{\circ}\text{C}$, $V_{IN} = 10\text{V}$, $I_{LOAD} = 5\text{ mA}$											V				
Line Regulation	$T_J = 25^{\circ}\text{C}$, $I_{LOAD} = 5\text{ mA}$, $V_{MIN} \leq V_{IN} \leq V_{MAX}$											mV				
Input Voltage												V				
Ripple Rejection	$f = 120\text{ Hz}$											dB				
Load Regulation, (Note 2)	$T_J = 25^{\circ}\text{C}$, $V_{IN} = 10\text{V}$, $5\text{ mA} \leq I_{LOAD} \leq I_D$											mV				
Output Voltage, (Note 1)	$-7.5\text{V} \leq V_{IN} \leq V_{MAX}$, $5\text{ mA} \leq I_{LOAD} \leq I_D$, $P \leq P_D$											V				
Quiescent Current	$V_{MIN} \leq V_{IN} \leq V_{MAX}$											mA				
Quiescent Current Change	$T_J = 25^{\circ}\text{C}$ $V_{MIN} \leq V_{IN} \leq V_{MAX}$ $5\text{ mA} \leq I_{LOAD} \leq I_D$											mA				
Output Noise Voltage	$T_A = 25^{\circ}\text{C}$, $C_L = 1\text{ }\mu\text{F}$, $I_L = 5\text{ mA}$, $V_{IN} = 10\text{V}$, $10\text{ Hz} \leq f \leq 100\text{ kHz}$											μV				
Long Term Stability												mV				
Thermal Resistance Junction to Case Junction to Ambient												$^{\circ}\text{C/W}$ $^{\circ}\text{C/W}$				

Note 1: This specification applies over –55°C ≤ T_J ≤ +150°C for the LM120 and 0°C ≤ T_J ≤ +125°C for the LM320.

Note 2: Regulation is measured at constant junction temperature. Changes in output voltage due to heating effects must be taken into account separately. To ensure constant junction temperature, low duty cycle, pulse testing is used. The LM120/LM320 series does have low thermal feedback, improving line and load regulation. On all other tests, even though power dissipation is internally limited, electrical specifications apply only up to P_D.

Note 3: For –5V 3 amp regulators, see LM145 data sheet.

Note 4: Thermal resistance of typically 85°C/W (in 400 linear feet air flow), 224°C/W (in static air) junction to ambient, of typically 21°C/W junction to case.

Note 5: Refer to RETS120-SH drawing for LM120H-5.0 or RETS120-5K drawing for LM120-5K military specifications.

— 12 Volt Regulators

Absolute Maximum Ratings

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications. (Note 4)

Power Dissipation
Input Voltage

Internally Limited
–35V

Input-Output Voltage Differential
Junction Temperatures
Storage Temperature Range
Lead Temperature (Soldering, 10 sec.)

30V
See Note 1
–65°C to +150°C
300°C

Electrical Characteristics

Order Numbers		Metal Can Package												Power Plastic Package			
		LM120K-12 (TO-3)				LM320K-12 (TO-3)				LM120H-12 (TO-39)				LM320H-12 (TO-39)			
		1A 20W		1A 20W		1A 20W		1A 20W		0.2A 2W		0.2A 2W		1A 15W			
Parameter	Design Output Current (I _O) Device Dissipation (P _D)		Conditions (Note 1)	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	Units	
Output Voltage	T _J = 25°C, V _{IN} = 17V, I _{LOAD} = 5 mA			–12.3	–12	–11.7	–12.4	–12	–11.6	–11.7	–12.3	–12	–12.4	–12	–11.6	–12	V
Line Regulation	T _J = 25°C, I _{LOAD} = 5 mA, V _{MIN} ≤ V _{IN} ≤ V _{MAX}				4	10		4	20			4		4	20		mV
Input Voltage				–32		–14	–32		–14	–32			–32		–14.5		V
Ripple Rejection	f = 120 Hz			56	80		56	80		56	80		56	80		dB	
Load Regulation, (Note 2)	T _J = 25°C, V _{IN} = 17V, 5 mA ≤ I _{LOAD} ≤ I _O				30	80		30	80		10	25		10	40		mV
Output Voltage, (Note 1)	14.5V ≤ V _{IN} ≤ V _{MAX} , 5 mA ≤ I _{LOAD} ≤ I _O , P ≤ P _D			–12.5		–11.5	–12.6		–11.4	–12.5		–11.5	–12.6		–11.4	–12.6	V
Quiescent Current	V _{MIN} ≤ V _{IN} ≤ V _{MAX}				2	4		2	4			2		2	4		mA
Quiescent Current Change	T _J = 25°C V _{MIN} ≤ V _{IN} ≤ V _{MAX} 5 mA ≤ I _{LOAD} ≤ I _O				0.1	0.4		0.1	0.4		0.05	0.4		0.05	0.4		mA
Output Noise Voltage	T _A = 25°C, C _L = 1 μF, I _L = 5 mA, V _{IN} = 17V, 10 Hz ≤ f ≤ 100 kHz				400			400				400		400			μV
Long Term Stability					12	120		12	120			12		12	120		mV
Thermal Resistance Junction to Case						3			3								°C/W
Junction to Ambient						35			35						Note 3 Note 3	4 50	°C/W

Note 1: This specification applies over –55°C ≤ T_J ≤ +150°C for the LM120 and 0°C ≤ T_J ≤ +125°C for the LM320.

Note 2: Regulation is measured at constant junction temperature. Changes in output voltage due to heating effects must be taken into account separately. To ensure constant junction temperature, low duty cycle, pulse testing is used. The LM120/LM320 series does have low thermal feedback, improving line and load regulation. On all other tests, even though power dissipation is internally limited, electrical specifications apply only up to P_D.

Note 3: Thermal resistance of typically 85°C/W (in 400 linear feet/min air flow), 224°C/W (in static air) junction to ambient, of typically 21°C/W junction to case.

Note 4: Refer to RETS120H-12 drawing for LM120H-12 or RETS120-12K drawing for LM120K-12 military specifications.

— 15 Volt Regulators

Absolute Maximum Ratings

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications. (Note 4)

Input-Output Voltage Differential
Junction Temperatures
Storage Temperature Range
Lead Temperature (Soldering, 10 sec.)

30V
See Note 1
–65°C to +150°C
300°C

Power Dissipation Internally Limited
Input Voltage
LM120/LM320
LM320T

–40V
–35V

Electrical Characteristics

Order Numbers		Metal Can Package										Power Plastic Package			
		LM120K-15 (TO-3)		LM320K-15 (TO-3)		LM120H-15 (TO-39)		LM320H-15 (TO-39)		LM320T-15 (TO-220)					
Parameter	Design Output Current (I _O) Device Dissipation (P _D)	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
Output Voltage	T _J = 25°C, V _{IN} = 20V, I _{LOAD} = 5 mA	–15.3	–14.7	–15.4	–14.6	–15.3	–14.7	–15	–14.6	–15.5	–14.5				
Line Regulation	T _J = 25°C, I _{LOAD} = 5 mA, V _{MIN} ≤ V _{IN} ≤ V _{MAX}		10	5	20		10	5	20		5		20	5	20
Input Voltage		–35	–17	–35	–17	–35	–17	–35	–17	–35	–17				
Ripple Rejection	f = 120 Hz	56	80	56	80	56	80	56	80	56	80				
Load Regulation, (Note 2)	T _J = 25°C, V _{IN} = 20V, 5 mA ≤ I _{LOAD} ≤ I _O		30		80		30		80		30		80		30
Output Voltage, (Note 1)	17.5V ≤ V _{IN} ≤ V _{MAX} , 5 mA ≤ I _{LOAD} ≤ I _O , P ≤ P _D	–15.5	–14.5	–15.6	–14.4	–15.5	–14.5		–15.6	–15.7	–14.4		–14.3		
Quiescent Current	V _{MIN} ≤ V _{IN} ≤ V _{MAX}		2		4		2		4		2		4		2
Quiescent Current Change	T _J = 25°C V _{MIN} ≤ V _{IN} ≤ V _{MAX} 5 mA ≤ I _{LOAD} ≤ I _O		0.1		0.4		0.1		0.4		0.05		0.4		0.1
Output Noise Voltage	T _A = 25°C, C _L = 1 μF, I _L = 5 mA, V _{IN} = 20V, 10 Hz ≤ f ≤ 100 kHz		400		400		400		400		400		400		400
Long Term Stability			15		150		15		150		15		150		30
Thermal Resistance Junction to Case Junction to Ambient			3		35		3		35		Note 3 Note 3		Note 3 Note 3		4 50










Note 1: This specification applies over –55°C ≤ T_J ≤ +150°C for the LM120 and 0°C ≤ T_J ≤ +125°C for the LM320.

Note 2: Regulation is measured at constant junction temperature. Changes in output voltage due to heating effects must be taken into account separately. To ensure constant junction temperature, low duty cycle, pulse testing is used. The LM120/LM320 series does have low thermal feedback, improving line and load regulation. On all other tests, even though power dissipation is internally limited, electrical specifications apply only up to P_D.

Note 3: Thermal resistance of typically 85°C/W (in 400 linear feet/min air flow), 224°C/W (in static air) junction to ambient, of typically 21°C/W junction to case.

Note 4: Refer to RETS120-15H drawing for LM120H-15 or RETS120-15K drawing for LM120K-15 military specifications.





Typical Performance Characteristics



*These curves for LM120.
Derate 25°C further for LM320.

TL/H/7767-4


Typical Performance Characteristics (Continued)



TL/H/7767-5

Typical Applications (Continued)

High Stability 1 Amp Regulator



TL/H/7767-6

Load and line regulation — 0.01% temperature stability — 0.2%

†Determines Zener current.


††Solid tantalum.

An LM120-12 or LM120-15 may be used to permit higher input voltages, but the regulated output voltage must be at least $-15V$ when using the LM120-12 and $-18V$ for the LM120-15.

**Select resistors to set output voltage. 2 ppm/°C tracking suggested.

Typical Applications (Continued)

Wide Range Tracking Regulator




TL/H/7767-7

*Resistor tolerance of R1 and R2 determine matching of (+) and (-) inputs.

**Necessary only if raw supply capacitors are more than 3" from regulators
An LM3086N array may substitute for Q1, D1 and D2 for better stability and tracking. In the array diode transistors Q5 and Q4 (in parallel) make up D2; similarly, Q1 and Q2 become D1 and Q3 replaces the 2N2222.

Variable Output



TL/H/7767-9


*Optional. Improves transient response and ripple rejection.

$$V_{OUT} = V_{SET} \frac{R1 + R2}{R2}$$

SELECT R2 AS FOLLOWS:

LM120-5	- 300Ω
LM120-12	- 750Ω
LM120-15	- 1k


Current Source



$$I_{OUT} = 1 \text{ mA} + \frac{5.0 \text{ V}}{R1}$$

TL/H/7767-8

± 15V, 1 Amp Tracking Regulators



TL/H/7767-12


Performance (Typical)

Load Regulation at $\Delta I_L = 1 \text{ A}$	10 mV	1 mV
Output Ripple, $C_{IN} = 3000 \mu\text{F}$, $I_L = 1 \text{ A}$	100 μVrms	100 μVrms
Temperature Stability	+ 50 mV	+ 50 mV
Output Noise 10 Hz $\leq f \leq 10 \text{ kHz}$	150 μVrms	150 μVrms

*Resistor tolerance of R4 and R5 determine matching of (+) and (-) outputs.

**Necessary only if raw supply filter capacitors are more than 2" from regulators.


Light Controllers Using Silicon Photo Cells



TL/H/7767-10

*Lamp brightness increases until $i_L = 5 \text{ V}/R1$ (i_L can be set as low as 1 μA).

†Necessary only if raw supply filter capacitor is more than 2" from LM320MP.




TL/H/7767-11

*Lamp brightness increases until $i_L = i_Q (1 \text{ mA}) + 5 \text{ V}/R1$.

†Necessary only if raw supply filter capacitor is more than 2" from LM320.


Connection Diagrams



Bottom View

TL/H/7767-13


Metal Can Package TO-39 (H)
 Order Number LM120H-5.0, LM120H-12, LM120H-15,
 LM120H-5.0/883, LM120H-12/883, LM120H-15/883,
 LM320H-5.0, LM320H-12 or LM320H-15
 See NS Package Number H03A



Bottom View

TL/H/7767-14

Steel Metal Can Package TO-3 (K)
 Order Number LM120K-5.0/883, LM120K-12/883,
 LM120K-15/883, LM320K-5.0, LM320K-12 or LM320K-15
 See NS Package Number K02A




Front View

TL/H/7767-17

Power Package TO-220 (T)
 Order Number LM320T-5.0, LM320T-12 or LM320T-15
 See NS Package Number T03B

Schematic Diagrams


-5V



TL/H/7767-18

Schematic Diagrams (Continued)

- 12V and - 15V



TL/H/7767-19