

NE/SE530 High Slew Rate Operational Amplifier

Product Specification

Linear Products


DESCRIPTION

The 530 is a new generation operational amplifier featuring a high slew rate combined with improved input characteristics. Internally compensated, the SE530 guarantees slew rates of $25V/\mu s$ with 2mV typical offset voltage. Industry standard pinout and internal compensation allow the user to upgrade system performance by directly replacing general purpose amplifiers such as the 741 and LF356 types.

FEATURES

- Gain bandwidth product — 3MHz
- $35V/\mu s$ slew rate (gain = -1)
- Internal frequency compensation
- Low input offset voltage 2mV typical
- Low input bias current — 65nA typical
- Short-circuit protection
- Offset null capability
- Large common-mode and differential voltage ranges


PIN CONFIGURATION



ORDERING INFORMATION

DESCRIPTION	TEMPERATURE RANGE	ORDER CODE
8-Pin Plastic DIP	0 to +70°C	NE530N
8-Pin Ceramic DIP	0 to +70°C	NE530FE
8-Pin Plastic DIP	-55°C to +125°C	SE530N
8-Pin Ceramic DIP	-55°C to +125°C	SE530FE

EQUIVALENT SCHEMATIC EACH AMPLIFIER



High Slew Rate Operational Amplifier

NE/SE530

ABSOLUTE MAXIMUM RATINGS

SYMBOL	PARAMETER	RATING	UNIT
V _{CC}	Supply voltage		
	SE530	± 22	V
	NE530	± 18	V
P _D MAX	Maximum power dissipation		
	T _A = 25°C (still air) ¹		
	F package	830	mW
	N package	1200	mW
V _{DIFF}	Differential input voltage	± 30	V
V _{IN}	Input voltage	± 15	V
T _A	Operating temperature range		
	SE530	-55 to +125	°C
	NE530	0 to +70	°C
T _{STG}	Storage temperature range	-65 to +150	°C
T _{SOLD}	Lead soldering temperature (10sec max)	300	°C
I _{SC}	Output short circuit	Indefinite	

NOTE:

1. Derate above 25°C, at the following rates:

F package at 6.7mW/°C

N package at 9.6mW/°C

DC ELECTRICAL CHARACTERISTICS T_A = 25°C, V_{CC} = ± 15V, unless otherwise specified.

SYMBOL	PARAMETER	TEST CONDITIONS	SE530			NE530			UNIT
			Min	Typ	Max	Min	Typ	Max	
V _{OS}	Input offset voltage	R _S ≤ 10kΩ Over temperature		0.7	4.0 5.0		2.0	6.0 7.0	mV mV
ΔV _{OS}	Temperature coefficient of input offset voltage	Over temperature		3	15		6		μV/°C
I _{OS}	Input offset current	Over temperature		5	20 40		15	40 80	nA nA
ΔI _{OS}	Input offset current	Over temperature		25			40		pA/°C
I _{BIAS}	Input bias current	Over temperature		45	80 200		65	150 200	nA nA
ΔI _{BIAS}	Input current	Over temperature		50			80		pA/°C
R _{IN}	Input resistance		3	10		1	6		MΩ
V _{CM}	Input common mode voltage range		± 12	± 13		± 12	± 13		V
A _{VOL}	Large signal voltage gain	R _L ≥ 2kΩ, V _O = ± 10V Over temperature	50 25	200		50 25	200		V/mV V/mV
V _{OUT}	Output voltage swing	R _L ≥ 10kΩ R _L ≥ 2kΩ	± 12 ± 10	± 14 ± 13		± 12 ± 10	± 14 ± 13		V V
I _{SC}	Output short-circuit current		10	25	50	10	25	50	mA
R _{OUT}	Output resistance			100			100		Ω
I _{CC}	Supply current	Over temperature		2.0 2.2	3.0 3.6		2.0 2.2	3.0	mA mA
CMRR	Common-mode rejection ratio	R _S ≤ 10kΩ Over temperature	70	90		70	90		dB
PSRR	Power supply rejection ratio	R _S ≤ 10kΩ Over temperature		30	150		30	150	μV/V

High Slew Rate Operational Amplifier

NE/SE530


AC ELECTRICAL CHARACTERISTICS $T_A = 25^\circ\text{C}$, $V_{CC} = \pm 15\text{V}$, unless otherwise specified.

SYMBOL	PARAMETER	TEST CONDITIONS	SE530			NE530			UNIT
			Min	Typ	Max	Min	Typ	Max	
t_R	Transient Response	To 0.1% (10V step)		0.06			0.06		μs
	Small-signal rise time			13			13		%
t_S	Small-signal overshoot			0.9			0.9		μs
	Settling time								
SR	Slew rate	$\pm 15\text{V}$ supply, $V_O = \pm 10\text{V}$, $R_L \geq 2\text{k}\Omega$							
	Unity gain inverting		25	35		20	35		$\text{V}/\mu\text{s}$
	Unity gain non-inverting		18	25		12	25		$\text{V}/\mu\text{s}$
BW	Power bandwidth	5% THD, $V_O = \pm 10\text{V}$, $R_L \geq 2\text{k}\Omega$	360	500		280	500		kHz
	Small-signal bandwidth	Open-loop		3			3		MHz
V_{NOISE}	Input noise voltage	$f = 1\text{kHz}$		30			30		$\text{nV}/\sqrt{\text{Hz}}$

High Slew Rate Operational Amplifier

NE/SE530

TYPICAL PERFORMANCE CHARACTERISTICS




High Slew Rate Operational Amplifier


NE/SE530

TYPICAL PERFORMANCE CHARACTERISTICS (Continued)


NE530 Open-Loop Gain and Phase vs Frequency




Gain Bandwidth Product and Phase Margin vs Load Capacity




Power Bandwidth




Input Voltage Step vs Settling Time to 10mV




Slew Rate — Voltage-Follower



Slew Rate (−1 Amplifier)





TYPICAL CIRCUIT CONNECTION





High Slew Rate Operational Amplifier

NE/SE530

TEST LOAD CIRCUITS

**NOTES:**

Pins not shown are not connected.
All resistor values are typical and in ohms.

Slew Rate and Settling Time**High Slew Rate — Inverting Amplifier****NOTES:**

Pins not shown are not connected.
All resistor values are typical and in ohms.
*Match to within 0.01%.
**Open for slew rate.

High Slew Rate — Voltage-Follower**Testing Slew Rate and Settling Time**

High Slew Rate Operational Amplifier

NE/SE530

VOLTAGE WAVEFORMS

