LINEAR INTEGRATED CIRCUIT



10W CAR RADIO AUDIO AMPLIFIER

The TDA 2003 has improved performance with the same pin configuration as the TDA 2002. The additional features of TDA 2002, very low number of external components, ease of assembly, space and cost saving, are maintained.

The device provides a high output current capability (up to 3.5A) very low harmonic and cross-over distortion.

Completely safe operation is guaranteed due to protection against DC and AC short circuit between all pins and ground, thermal over-range, load dump voltage surge up to 40V, polarity inversion and fortuitous open ground.

ABSOLUTE MAXIMUM RATINGS

V,	Peak supply voltage (50 ms)	40	v
V,	DC supply voltage	28	V
V,	Operating supply voltage	18	V
10	Output peak current (repetitive)	3.5	Α
l _o	Output peak current (non repetitive)	4.5	Α
P _{tot}	Power dissipation at $T_{case} = 90^{\circ}C$	20	W
T_{stg},T_{j}	Storage and junction temperature	-40 to 150	°C

ORDERING NUMBERS: TDA 2003H TDA 2003V

MECHANICAL DATA

14.2

0.5 14.8 18.7 2.8 5 15.8 15.8 15.8 15.8 15.8 16.8 10.4

Dimensions in mm





CONNECTION DIAGRAM

(top view)



SCHEMATIC DIAGRAM



THERMAL DATA

R _{th i-case}	Thermal resistance junction-case	max	3	°C/W



DC TEST CIRCUIT





ELECTRICAL CHARACTERISTICS ($V_s = 14.4V$, $T_{amb} = 25^{\circ}C$ unless otherwise specified)

Parameter	Test conditions	Min.	Typ.	Max.	Unit
DC CHARACTERISTICS (Refer t	o DC test circuit)				
V Supply voltage				10	<u> </u>

v _s	Supply voltage	8		18	
V _o	Quiescent output voltage (pin 4)	6.1	6.9	7.7	v
۱a	Quiescent drain current (pin 5)		44	50	mA

AC CHARACTERISTICS (Refer to AC test circuit, $G_v = 40 \text{ dB}$)

Po	Output power	d = 10% f = 1 kHz	R _L = 4Ω R _L <u>≡</u> 2Ω R _L = 3.2Ω R _L = 1.6Ω	5.5 9	6 10 7.5 12	≤ ≤ ≤ ≤
V _{i(rms)}	Input saturation voltage			300		mν
Vi	Input sensitivity	$f = 1 \text{ kHz}$ $P_o = 0.5W$ $P_o = 6W$ $P_o = 0.5W$ $P_o = 10W$	R _L = 4Ω R _L = 4Ω R _L = 2Ω R _L = 2Ω		14 55 10 50	> > > > > > > > > > > > > > > > > > >



ELECTRICAL CHARACTERISTICS (continued)

	Parameter	Test conditions	Min.	Тур.	Max.	Unit
B Frequency response (-3 dB)		$P_o = 1W$ $R_L = 4\Omega$	40 to 15,000		00	Hz
d	Distortion			0.15 0.15		% %
Ri	Input resistance (pin 1)	f = 1 kHz	70	150		kΩ
Gv	· Voltage gain (open loop)	f = 1 kHz f = 10 kHz		80 60		dB dB
Gv	Voltage gain (closed loop)	f = 1 kHz R _L = 4Ω	39.5	40	40.5	dB
e _N	Input noise voltage (0)			1	5	<i>μ</i> ∨
ĪN	Input noise current (0)		5	60	200	pА
η	Efficiency			69 65		%
SVR	Supply voltage rejection	$f = 100 \text{ Hz}$ $V_{ripple} = 0.5V$ $R_g = 10 \text{ k}\Omega$ $R_L = 4\Omega$	30	36	-	dB

(0) Filter with noise bandwidth: 22 Hz to 22 kHz

















quency Vg =14.4V Gv =40dB RL = 2 and 4Ω (%) -----1.2 -----0.8 0.4 2.5W 0 107 103 10.4 f(Hz) 10

Fig. 8 - Distortion vs. fre-

Fig. 9 - Supply voltage rejection vs. voltage gain



Fig. 10 – Supply voltage rejection vs. frequency



Fig. 11 - Power dissipation and efficiency vs. output power $(R_L = 4\Omega)$



Fig. 12 - Power dissipation and efficiency vs. output power $(R_{\perp} = 2\Omega)$





Fig. 13 – Maximum power dissipation vs. supply voltage (sine wave operation)



Fig. 14 - Maximum allowable power dissipation vs. ambient temperature







APPLICATION INFORMATION

Fig. 16 - Typical application circuit





Fig. 19 – P.C. board and component layout for the circuit of fig. 18 (1:1 scale)



Fig. 18 – 20W bridge configuration application circuit (*)





APPLICATION INFORMATION (continued)



Fig. 22 - P.C. board and component layout for the low-cost bridge amplifier of fig. 20, in stereo version (1:1 scale)



BUILT-IN PROTECTION SYSTEMS

Load dump voltage surge

The TDA 2003 has a circuit which enables it to withstand a voltage pulse train, on pin 5, of the type shown in fig. 23.

If the supply voltage peaks to more than 40V, then an LC filter must be inserted between the supply and pin 5, in order to assure that the pulses at pin 5 will be held within the limits shown in fig. 23. A suggested LC network is shown in fig. 24. With this network, a train of pulses with amplitude up to 120V and width of 2 ms can be applied at point A. This type of protection is ON when the supply voltage (pulsed or DC) exceeds 18V. For this reason the maximum operating supply voltage is 18V.



Short-circuit (AC and DC conditions)

The TDA 2003 can withstand a permanent short-circuit on the output for a supply voltage up to 16V.

Polarity inversion

High current (up to 5A) can be handled by the device with no damage for a longer period than the blow-out time of a quick 1A fuse (normally connected in series with the supply).

This feature is added to avoid destruction if, during fitting to the car, a mistake on the connection of the supply is made.

Open ground

When the radio is in the ON condition and the ground is accidentally opened, a standard audio amplifier will be damaged. On the TDA 2003 protection diodes are included to avoid any damage.

Inductive load

A protection diode is provided between pin 4 and 5 (see the internal schematic diagram) to allow use of the TDA 2003 with inductive loads.

In particular, the TDA 2003 can drive a coupling transformer for audio modulation.

DC voltage

The maximum operating DC voltage on the TDA 2003 is 18V.

However the device can withstand a DC voltage up to 28V with no damage. This could occur during winter if two batteries were series connected to crank the engine.

Thermal shut-down

The presence of a thermal limiting circuit offers the following advantages:

- 1) an overload on the output (even if it is permanent), or an excessive ambient temperature can be easily withstood.
- 2) the heat-sink can have a smaller factor of safety compared with that of a conventional circuit. There is no device damage in the case of excessive junction temperature: all that happens is that P_o (and therefore P_{tot}) and I_d are reduced (figs. 25 and 26).





PRATICAL CONSIDERATIONS

Printed circuit board

The layout shown in fig. 17 is recommended. If different layouts are used, the ground points of input 1 and input 2 must be well decoupled from the ground of the output through which a rather high current flows.

TDA 2003

Assembly suggestion

No electrical insulation is required between the package and the heat-sink. Pin length should be as short as possible. The soldering temperature must not exceed 260°C for 12 seconds.

Application suggestions

The recommended component values are those shown in the application circuits of fig. 16. Different values can be used. The following table is intended to aid the car-radio designer.

Component	Recommended value	Purpose	Larger than recommended value	Smaller than recommended value
C1	2.2 μF	Input DC decoupling		Noise at switch-on, switch-off
C2	470 μF	Ripple rejection		Degradation of SVR
С3	0.1 μF	Supply bypassing		Danger of oscillation
C4	1000 μF	Output coupling to load		Higher low frequency cutoff
C5	0.1 µF	Frequency stability		Danger of oscillation at high frequencies with inductive loads
c _x	$\cong \frac{1}{2 \pi B R 1}$	Upper frequency cutoff	Lower bandwidth	Larger bandwidth
R1	(G _v -1) • R2	Setting of gain		Increase of drain current
R2	2.2 Ω	Setting of gain and SVR	Degradation of SVR	
R3	1 Ω	Frequency stability	Danger of oscillation at high frequencies with inductive loads	
R _X	≅ 20 R2	Upper frequency cutoff	Poor high frequency attenuation	Danger of oscillation