

# Schottky Diodes

TYPE NO.	CONFIGURATION	$V_{RRM}$	$I_F$	$V_F @ I_F$		$t_{rr}$	CT
		(V)	* $I_O$ (mA)	(V)	(mA)	(ns)	*TYP (pF)
		MAX	MAX	MAX		MAX	MAX

**SUPER**<sup>TM</sup>  
**mini**



## SOD-323 Case

### High Current

<b>CMDSH-3</b>	SINGLE	30	100*	0.55	50	5.0	7.0*
<b>CMDSH2-3</b>	SINGLE	30	200*	0.55	200	-	15*



## SOT-23 Case

### Low Current

<b>CMPD6263</b>	SINGLE	70	15	0.41	1.0	1.0	2.0
<b>CMPD6263A</b>	DUAL, COMMON ANODE	70	15	0.41	1.0	1.0	2.0
<b>CMPD6263C</b>	DUAL, COMMON CATHODE	70	15	0.41	1.0	1.0	2.0
<b>CMPD6263S</b>	DUAL, IN SERIES	70	15	0.41	1.0	1.0	2.0

### High Current

<b>CMPSH-3</b>	SINGLE	30	100	0.45	15	5.0	7.0*
<b>CMPSH-3A</b>	DUAL, COMMON ANODE	30	100	0.45	15	5.0	7.0*
<b>CMPSH-3C</b>	DUAL, COMMON CATHODE	30	100	0.45	15	5.0	7.0*
<b>CMPSH-3S</b>	DUAL, IN SERIES	30	100	0.45	15	5.0	7.0*