

TRIACS


- GLASS PASSIVATED CHIP
- I_{GT} SPECIFIED IN FOUR QUADRANTS
- INSULATING VOLTAGE 2500 V_{RMS}
- UL RECOGNIZED (E81734)

DESCRIPTION

This new design of plastic insulated power triacs offers maximum efficiency with maximum ease of mounting.

ADVANTAGES

- NO TAPPING REQUIRED FOR FIXING
- EXCELLENT THERMAL IMPEDANCE AND HIGH RELIABILITY CONSTRUCTION


ABSOLUTE RATINGS (limiting values)

Symbol	Parameter		Value	Unit
$I_{T(RMS)}$	RMS on-state Current (360° conduction angle)	$T_C = 75^\circ C$	40	A
I_{TSM}	Non Repetitive Surge Peak on-state Current (T_j initial = 25 °C · Half sine wave)	$t = 8.3$ ms	315	A
		$t = 10$ ms	300	
$I^2 t$	$I^2 t$ Value for Fusing	$t = 10$ ms	450	A ² s
di/dt	Critical Rate of Rise of on-state Current (1)	Repetitive F = 50 Hz	10	A/μs
		Non Repetitive	50	
T_{stg} T_j	Storage and Operating Junction Temperature Range		- 40 to 125	°C
			- 40 to 125	°C

Symbol	Parameter	BTA 41-					Unit
		200A	400A	600A	700A	800A	
V_{DRM}	Repetitive Peak off-state Voltage (2)	200	400	600	700	800	V

(1) $I_G = 1.5$ A di/dt = 1 A/μs

(2) $T_j = 125^\circ C$.

THERMAL RESISTANCES

Symbol	Parameter	Value	Unit
$R_{th(j-a)}$	Junction to Ambient	50	°C/W
$R_{th(c-h)}$	Contact (case-heatsink) with Grease	0.2	°C/W
$R_{th(j-c)}$ DC	Junction to Case for DC	1.2	°C/W
$R_{th(j-c)}$ AC	Junction to Case for 360 ° Conduction Angle (F = 50 Hz)	0.9	°C/W

GATE CHARACTERISTICS (maximum values)

$P_{GM} = 40 \text{ W}$ ($t_p = 10 \mu\text{s}$) $I_{GM} = 10 \text{ A}$ ($t_p = 10 \mu\text{s}$)

$P_{G(AV)} = 1 \text{ W}$ $V_{GM} = 16 \text{ V}$ ($t_p = 10 \mu\text{s}$)


ELECTRICAL CHARACTERISTICS

Symbol	Test Conditions	Quadrants	Min.	Typ.	Max.	Unit
I_{GT}	$T_j = 25 \text{ }^\circ\text{C}$ $V_D = 12 \text{ V}$ $R_L = 33 \text{ } \Omega$ Pulse Duration > 20 μs	I-II-III	1		100	mA
		IV	1		150	
V_{GT}	$T_j = 25 \text{ }^\circ\text{C}$ $V_D = 12 \text{ V}$ $R_L = 33 \text{ } \Omega$ Pulse Duration > 20 μs	I-II-III-IV			1.5	V
V_{GD}	$T_j = 125 \text{ }^\circ\text{C}$ $V_D = V_{DRM}$ $R_L = 3.3 \text{ k}\Omega$	I-II-III-IV	0.2			V
I_H^*	$T_j = 25 \text{ }^\circ\text{C}$ $I_T = 500 \text{ mA}$ Gate Open			30	100	mA
I_L	$T_j = 25 \text{ }^\circ\text{C}$ $V_D = 12 \text{ V}$ $I_G = 300 \text{ mA}$ Pulse Duration > 20 μs	I-II-III-IV			150	mA
V_{TM}^*	$T_j = 25 \text{ }^\circ\text{C}$ $I_{TM} = 60 \text{ A}$ $t_p = 10 \text{ ms}$				1.8	V
I_{DRM}^*	$T_j = 125 \text{ }^\circ\text{C}$ V_{DRM} Specified			1.5	6	mA
dv/dt^*	$T_j = 125 \text{ }^\circ\text{C}$ Gate Open Linear Slope up to $V_D = 67\% V_{DRM}$		250			V/ μs
$(dv/dt)_c^*$	$T_C = 75 \text{ }^\circ\text{C}$ $V_D = V_{DRM}$ $I_T = 60 \text{ A}$ $(di/dt)_c = 18 \text{ A/ms}$		10			V/ μs
t_{gt}	$T_j = 25 \text{ }^\circ\text{C}$ $V_D = V_{DRM}$ $I_T = 60 \text{ A}$ $I_G = 1 \text{ A}$ $di_G/dt = 10 \text{ A}/\mu\text{s}$	I-II-III-IV		2.5		μs

* For either polarity of electrode A₂ voltage with reference to electrode A₁.

PACKAGE MECHANICAL DATA

TOP 3 Plastic



Cooling method : by conduction (method C)
 Marking : type number
 Weight : 5 g




Fig. 1 - Maximum mean power dissipation versus RMS on-state current (F = 60 Hz).




Fig. 2 - Correlation between maximum mean power dissipation and maximum allowable temperatures (T_{amb} and T_{case}) for different thermal resistances heatsink + contact.




Fig. 3 - RMS on-state current versus case temperature.




Fig. 5 - Relative variation of gate trigger current and holding current versus junction temperature.




Fig. 4 - Thermal transient impedance junction to case and junction to ambient versus pulse duration.




Fig. 6 - Non repetitive surge peak on-state current versus number of cycles.




Fig.7 - Non repetitive surge peak on-state current for a sinusoidal pulse with width : $t \leq 10$ ms, and corresponding value of I^2t .




Fig.8 - On-state characteristics (maximum values).