


SENSITIVE GATE TRIACS

- GLASS PASSIVATED CHIP
- I_{GT} SPECIFIED IN FOUR QUADRANTS
- AVAILABLE IN INSULATED VERSION → BTA SERIES (INSULATING VOLTAGE 2500 V_{RMS}) OR IN UNINSULATED VERSION → BTB SERIES
- UL RECOGNIZED FOR BTA SERIES (E81734)


DESCRIPTION

New range suited for applications such as phase control and static switching.

ABSOLUTE RATINGS (limiting values)

Symbol	Parameter		Value	Unit
$I_{T(RMS)}$	RMS on-state Current (360° conduction angle)	$T_C = 75\text{ °C}$	6	A
I_{TSM}	Non Repetitive Surge Peak on-state Current (T_j initial = 25 °C - Half sine wave)	$t = 8.3\text{ ms}$	63	A
		$t = 10\text{ ms}$	60	
I^2t	I^2t Value for Fusing	$t = 10\text{ ms}$	18	A ² s
di/dt	Critical Rate of Rise of on-state Current (1)	Repetitive F = 50 Hz	10	A/μs
		Non Repetitive	50	
T_{stg} T_j	Storage and Operating Junction Temperature Range		- 40 to 150	°C
			- 40 to 110	°C

Symbol	Parameter	BTA/BTB 06-					Unit
		200T	400T	600T	700T	800T	
V_{DRM}	Repetitive Peak off-state Voltage (2)	200	400	600	700	800	V

(1) $I_G = 50\text{ mA}$ $di_G/dt = 1\text{ A}/\mu\text{s}$

(2) $T_j = 110\text{ °C}$.

THERMAL RESISTANCES

Symbol	Parameter	Value	Unit
$R_{th(j-a)}$	Junction to Ambient	60	°C/W
$R_{th(j-c)}\text{ DC}$	Junction to Case for DC	5.8	°C/W
$R_{th(j-c)}\text{ AC}$	Junction to Case for 360 ° Conduction Angle (F = 50 Hz)	4.3	°C/W

GATE CHARACTERISTICS (maximum values)

$P_{GM} = 40 \text{ W}$ ($t_p = 10 \mu\text{s}$) $I_{GM} = 4 \text{ A}$ ($t_p = 10 \mu\text{s}$)
 $P_{G(AV)} = 1 \text{ W}$ $V_{GM} = 16 \text{ V}$ ($t_p = 10 \mu\text{s}$)


ELECTRICAL CHARACTERISTICS

Symbol	Test Conditions			Quadrants	Min.	Typ.	Max.	Unit
I_{GT}	$T_j = 25 \text{ }^\circ\text{C}$	$V_D = 12 \text{ V}$	$R_L = 33 \text{ }\Omega$	I-II-III-IV			5	mA
V_{GT}	$T_j = 25 \text{ }^\circ\text{C}$	$V_D = 12 \text{ V}$	$R_L = 33 \text{ }\Omega$	I-II-III-IV			1.5	V
V_{GD}	$T_j = 110 \text{ }^\circ\text{C}$	$V_D = V_{DRM}$	$R_L = 3.3 \text{ k}\Omega$	I-II-III-IV	0.2			V
I_{H^*}	$T_j = 25 \text{ }^\circ\text{C}$	$I_T = 100 \text{ mA}$	Gate Open				15	mA
I_L	$T_j = 25 \text{ }^\circ\text{C}$	$V_D = 12 \text{ V}$	$I_G = 10 \text{ mA}$	I-III-IV		15		mA
				II		30		
V_{TM}^*	$T_j = 25 \text{ }^\circ\text{C}$	$I_{TM} = 8.5 \text{ A}$	$t_p = 10 \text{ ms}$				1.65	V
I_{DRM}^*	V_{DRM} Specified						0.01	mA
							0.75	
dv/dt^*	$T_j = 110 \text{ }^\circ\text{C}$	Gate Open				10		V/ μs
	Linear Slope up to $V_D = 67\% V_{DRM}$							
$(dv/dt)_c^*$	$T_C = 75 \text{ }^\circ\text{C}$	$V_D = V_{DRM}$	$I_T = 8.5 \text{ A}$			1		V/ μs
	$(di/dt)_c = 2.7 \text{ A/ms}$							
t_{gt}	$T_j = 25 \text{ }^\circ\text{C}$	$V_D = V_{DRM}$	$I_T = 8.5 \text{ A}$	I-II-III-IV		2		μs
	$I_G = 20 \text{ mA}$							
	$di_G/dt = 0.25 \text{ A}/\mu\text{s}$							

* For either polarity of electrode A_2 voltage with reference to electrode A_1 .

PACKAGE MECHANICAL DATA

TO 220 AB Plastic



Cooling method : by conduction (method C)
 Marking : type number
 Weight : 2 g.




Fig. 1 - Maximum mean power dissipation versus RMS on-state current (F = 60 Hz).




Fig. 2 - Correlation between maximum mean power dissipation and maximum allowable temperatures (T_{amb} and T_{case}) for different thermal resistances heatsink + contact.




Fig. 3 - RMS on-state current versus case temperature.




Fig. 4 - Thermal transient impedance junction to case and junction to ambient versus pulse duration.




Fig. 5 - Relative variation of gate trigger current and holding current versus junction temperature.




Fig. 6 - Non repetitive surge peak on-state current versus number of cycles.




Fig.7 - Non repetitive surge peak on-state current for a sinusoidal pulse with width : $t \leq 10$ ms, and corresponding value of I^2t .




Fig.8 - On-state characteristics (maximum values).