


Rectifier Diodes

VRM:100~1000V Io:1.5~15A


FMM/CTM/RB/LB

Rating/ Characteristics	Absolute Maximum Ratings						Electrical Characteristics (Ta = 25°C)				Others		
	VRSM (V)	VRM (V)	Io (A)	IFSM (A)	Tj (°C)	Tstg (°C)	VF (V)	IR (μA)	IR(H) (μA)	Outline Drawing	Weight(g)	Taping	Internal Connections
Type No.			With Fin	50Hz Half Sine Wave Single Pulse			max	IF (A)	VR=VRM max	VR=VRM Ta=100°Cmax			
FMM-22S, R	250	200	10	100	-40~+150		1.1	5.0		100	⑱	2.1	S Type R Type Rth(j-t) 4.0°C/Wmax
FMM-24S, R	450	400											
FMM-26S, R	650	600											
CTM-21S, R	—	100	8				1.3	5.0		50	⑲	2.6	S Type R Type
CTM-22S, R	—	200											
CTM-24S, R	—	400											
CTM-26S, R	—	600											
CTM-32S, R	250	200	15	120	-40~+140		1.2	10		100	⑳	6.1	R Type
CTM-34S, R	450	400											
RB-150	70	50	1.5 (w/o Fin)	40	-40~+140		0.95	1.0	10		㉑	1.8	~ - + ~
RB-151	150	100											
RB-152	250	200											
RB-154	450	400											
RB-156	650	600											
RB-158	850	800											
LB-156	650	600											
RB-401	150	100	4.0	80	-40~+150		0.95			100	㉒	5.0	~ - + ~
RB-402	250	200											
RB-404	450	400											
RB-406	650	600											
RB-40C	1050	1000											
RB-601	150	100	6.0	180	-40~+150		0.5			100	㉓	9.2	~ - + ~
RB-602	250	200											
RB-604	450	400											
RB-606	650	600											


Outline Drawing ⑱




Outline Drawing ⑲




Outline Drawing ⑳




Outline Drawing ㉑




Outline Drawing ㉒



Outline Drawing ㉓







Outline Drawing ㉔





⑱~㉔ Plastic Molded, Flammability: UL94V-0 or Equivalent




CTM-2 Series






CTM-22U/24U Series





CTM-3 Series





RB-15 Series



RB-40, Series



RB-60 Series




Symbols/trr Measurement Circuit

Symbols

V_{RSM}	Peak Reverse Surge Voltage	I_{RSM}	Peak Reverse Surge Current	T_{stg}	Storage Temperature
V_{RM}	Peak Reverse Voltage	I_R	Reverse Current	t_{rr}	Reverse Recovery Time
V_{P-P}	Reverse Voltage (Peak to Peak)	I_{RP}	Peak Reverse Current	C_t	Total Capacitance Between Terminals
V_R	Reverse Voltage	$I_{R(H)}$	Reverse Current (High Temperature)	$R_{th(j-c)}$	Thermal Resistance, Junction to Case
V_F	Forward Voltage	I_Z	Avalanche Current	α_Z	Temperature Coefficient of Breakdown Voltage
V_B	Breakdown Voltage	I_{ZSM}	Allowable Avalanche Current	R_Z	Equivalent Resistance of Breakdown Region
I_o	Average Rectified Forward Current	T_a	Ambient Temperature	$P_{F(AV)}$	Average Forward Power Dissipation
I_F	Forward Current	T_j	Junction Temperature	I_t^*	I_t^* limiting Value
$I_{F(AV)}$	Average Forward Current	T_{opr}	Operating Ambient Temperature		
I_{FSM}	Peak Forward Surge Current	T_c	Case Temperature		

Reverse Recovery Time Measurement Circuit



Taping Specifications

Excluding High Voltage Diodes

Designation	Dimension (in mm)	Packaging Dimension and Marking	Quantity
<p>V</p> <p>Add Suffix [V] to Type No.</p>	<p>Tape Carrier Method</p> <p>(1) Right side of taping direction is cathode. (2) Place electrode side down when casing. (3) Provide leader tape of 150~200mm at beginning of tape. (4) Provide space of more than 10 pitches each for beginning and end of tape.</p>	<p>Reel</p> <p>Marking of Type No., Lot No. and Quantity</p>	<p>1,800 pcs per reel</p>
<p>V</p> <p>Add Suffix [V] to type No.</p>	<p>Axial Taping</p>	<p>Reel</p> <p>Markings of Type No., Lot No. and Quantity</p>	<p>5,000 pcs per reel (2.7φ body)</p> <p>3,000 pcs per reel (4.0φ body)</p>


Taping Specifications

Designation	Dimension (in mm)	Packaging Dimension and Marking	Quantity
<p>V1</p> <p>Add Suffix [V1] to Type No.</p>		<p>Ammunition Pack</p>	<p>2,000 pcs per box (2.7 φ body)</p> <p>1,000 pcs per box (4.0 φ body)</p>
<p>VO</p> <p>Add Suffix [VO] to Type No.</p>		<p>Ammunition Pack</p>	<p>2,000 pcs per box (2.7 φ body)</p> <p>(2.4 φ body)</p>
<p>V3</p> <p>Add Suffix [V3] to Type No.</p>		<p>Reel</p>	<p>1,500 pcs per reel (5.2 φ body)</p>
<p>V4</p> <p>Add Suffix [V4] to Type No.</p>		<p>Ammunition Pack</p>	<p>1,000 pcs per box (5.2 φ body)</p>
<p>W</p> <p>Add Suffix [W] to Type No.</p>		<p>Ammunition Pack</p>	<p>4,000 pcs per box (2.7 φ body)</p> <p>(0.6 φ lead)</p>
<p>WS</p> <p>Add Suffix [WS] to Type No.</p>		<p>Ammunition Pack</p>	<p>2,500 pcs per box (2.4 φ body)</p>
<p>WK</p> <p>Add Suffix [WK] to Type No.</p>		<p>Ammunition Pack</p>	<p>2,500 pcs per box (2.4 φ body)</p>

6
 ДІЯЄ НАВЕДЕНІЙ СОБЛІДАНЬОЇ В ІЇХ КОМПОНЕНТАХ НАПЛИВІСНИКІВ.


Marking Guide

1 Small TMD




- ① Type Designation (In abbreviation)
AM01 is abbreviated as M.
- ② Class Designation
Z: 200V, No Letter: 400V, A: 600V
- ③ A: Year (Last Number of AD Year)
B: Month (Jan. to Sept. are represented by numbers 1 to 9 respectively, and Oct., Nov., and Dec. are abbreviated as O, N and D respectively)
- ④ Cathode Band: Successive Band, however AU02 Type is Non-Successive Band.

6 TO220 Type (FM or CT Type)




- ① Type Designation
Show FMU-12S as FMU12S.
- ② Polarity: Rectifier Symbols
- ③ Lot Number (Laser Marking)
1st : Year (Last Number of AD Year)
2nd : Month (0~9, O, N, D)
3rd, 4th: Day

2 E/EO Type TMD




- ① Type Designation (In abbreviation)
EM01 is abbreviated as MO, EM2 is abbreviated as M2.
- ② Class Designation
Z: 200V, No Letter: 400V, A: 600V
B: 800 V, C: 1000V, F: 1500V
However, EU02A to be marked 2A, and EU2YX to be marked Y.
- ③ Abbreviations Representing Production Period
A: Year (Last Number of AD Year)
B: Month (1~9, O, N, D)
- ④ Production Period Divided in 3 ten day terms
• : 1st 10days •• : 2nd 10days ••• : 3rd 10days

7 TO220 Type (FM or CT Type, single chip)




- ① Type Designation: Omit Last Letter
Show FML-G12S as FMLG12.
- ② Last Letter of Type Designation
- ③ Polarity: Rectifier Symbols
- ④ Lot Number (Laser Marking)
1st : Year (Last Number of AD Year)
2nd : Month (0~9, O, N, D)
3rd, 4th: Day

3 R Type TMD



- ① Type Designation: Mark in 2 sets
- ② Production Period: Mark in 4 sets
A: Year (Last Number of AD Year)
B: Month (1~9, O, N, D)
- ③ Production Period Divided in 3 ten day terms
• : 1st 10days •• : 2nd 10days ••• : 3rd 10days
- ④ Cathode Band Color: Silver: For Power Supply
Yellow: For Middle Speed
Red : For High Speed and Ultra-High Speed


8 TO3P Type (FM or CT Type)



- ① Type shown in full designation
However, CTB-34/34S/34M are marked as CTB-34, CTU-G3DR is marked as CTUG3DR.
- ② Polarity: Rectifier Symbols
- ③ Lot Number:
1) M, U, G and L Types
First Number : Last Digit of AD Year
Second Number : Month
Third and Fourth Numbers: Day
Fifth Number : None
2) For types CTB-34/34S/34M, the fifth letter shows type designation. If no fifth number, the type is CTB-33 or CTB-34.
3) Marking Color: Silver


4 RB40/60

(RB40 Series)




- ① Peak Reverse Voltage Designation
1, 2, 4, 6, C
Production Period
- ② Year (Last Number of AD Year)
- ③ Month (1~9, O, N, D)
- ④ Divided in 3 ten day terms
A: 1st 10days, B: 2nd 10days
C: 3rd 10days
Color Designation: Silver

(RB60 Series)




- Dot Designation RB601 Violet
RB602 No Color
RB604 Blue
RB606 White

9 MI-10/15 Type




- ① MI-10/15 is die-stamped on the top of the case.
- ② Rectifier Symbols
- ③ Lot Number:
First Number : Peak Reverse Voltage:
(Letter) 0=50V, 1=100V, 2=200V,
4=400V, 6=600V, C=1000V
Second Number : Last Digit of AD Year
Third Number : Month
Fourth and Fifth Numbers: Day
Sixth Number : Production number and
U: Voltage Doubler Type

5 RBV/RBA



- ① Type Designation
- ② Lot Number
1st : Year (Last Number of AD Year)
2nd: Month (1~9, O, N, D)
3rd : Divided 1~3 ten day Terms
A: 1st 10 days B: 2nd 10 days
C: 3rd 10 days
- ③ In-Put Designation

10 SFP Type



- ① Type Designation:
SFPB-64 is abbreviated at B64.
- ② Cathode Band