



Dimensions are in inch [metric] units.

**FEATURES**

- Ideal for electron detection
- Circular active area
- 100% internal QE

**ELECTRO-OPTICAL CHARACTERISTICS AT 25°C**

PARAMETERS	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Active Area			15		mm <sup>2</sup>
Responsivity, $\mathcal{R}$	(see graphs on the next page)	0.07	0.08	0.09	A/W
Shunt Resistance, $R_{SH}$	$V_R = \pm 10mV$	10			MOhms
Reverse Breakdown Voltage, $V_R$	$I_R = 1\mu A$	5			Volts
Capacitance, C	$V_R = 0V$		1.5		nF
Rise Time	$V_R = 2V, R_L = 50\Omega$			2	usec

**THERMAL PARAMETERS**

STORAGE AND OPERATING TEMPERATURE RANGE	
Ambient <sup>1</sup>	-10° TO 40°C <sup>1</sup>
Nitrogen or Vacuum	-20°C TO 80°C
Maximum Junction Temperature	70°C
Lead soldering temperature <sup>2</sup>	260°C

<sup>1</sup>Temperatures exceeding these parameters may create oxide growth on the active area. Over time responsivity to low energy radiation and wavelengths below 150nm will be compromised.

<sup>2</sup>0.080" from case for 10 seconds.

Shipped with temporary cover to protect photodiode and wire bond.  
Review Opto Diode "Handling Precautions for IRD Detectors" prior to removing cover.

